

TECHNICAL DATA SHEET

SULFISOL 10 E228

FORMULATION

Pulphurous anhydride solution dissolved in water partially neutralized
Potassium bisulfite

FIELD OF APPLICATION

Sulphiting of wines and musts

APPLICATION RATE AND DIRECTIONS FOR USE

1cL/hL gives 1g of SO₂ and 0.6g of potassium
Regulation: maximum dosage subject to regulation. Refer to regulation texts.

SPECIFICATIONS

Aspect	liquid	Density	1130 ± 15
Colour	Limpid yellow	SO₂	102 ± 2g/l
Potassium	62g/L	pH	5,3 ± 0,5
Lead	< 5 ppm	Chlorides	< 0,1%
Iron	< 10 ppm	Arsenic	< 2 ppm
Mercury	< 1ppm	Selenium	< 5 ppm

STORAGE

Store in a cool (13-15°C) and airy place. Store in its original, airtight sealed package.
Respect the optimal date of use written on packaging.
Use quickly after opening

PACKAGING

5.5kg, 22kg, 132kg and 1000kg cans

**IN ACCORDANCE WITH THE CURRENT INTERNATIONAL OENOLOGICAL CODEX –
FOR OENOLOGICAL USAGE FOR THE ELABORATION OF PRODUCTS
INTENDED FOR DIRECT HUMAN CONSUMPTION**

CC-26.11.12

