

## TECHNICAL DATA SHEET

# SULFISOL 6 E220

### FORMULATION

Pur sulphurous anhydride solution

### FIELD OF APPLICATION

Sulphiting of wines and musts

### APPLICATION RATE AND DIRECTIONS FOR USE

1cL/hL gives 0.6g of SO<sub>2</sub>

Regulation: maximum dosage subject to regulation. Refer to regulation texts.

### SPECIFICATIONS

<b>Aspect</b>	liquid	<b>Density</b>	1032 ± 3
<b>Colour</b>	Limpid	<b>SO<sub>2</sub></b>	65 ± 2g/l
<b>Olor</b>	Pungent, suffocating	<b>pH</b>	5,3 ± 0,5
<b>Lead</b>	< 5 ppm	<b>Chlorides</b>	< 0,1%
<b>Iron</b>	< 50 ppm	<b>Arsenic</b>	< 2 ppm
<b>Mercury</b>	< 1ppm	<b>Selenium</b>	< 10ppm

### STORAGE

Store in a cool (13-15°C) and airy place. Store in its original, airtight sealed package.

Respect the optimal date of use written on packaging.

Use quickly after opening

### PACKAGING

5kg, 20kg and 120kg cans

**IN ACCORDANCE WITH THE CURRENT INTERNATIONAL OENOLOGICAL CODEX –  
FOR OENOLOGICAL USAGE FOR THE ELABORATION OF PRODUCTS  
INTENDED FOR DIRECT HUMAN CONSUMPTION**

GR-21/02/2011



## TECHNICAL DATA SHEET

